



**SPECIFICATIONS**

PISTON DIA	118 mm	
PISTON STROKE	16 mm	
PISTON THRUST (OIL PRESSURE AT 3.1 MPa)	PUSH	25.3 kN
	PULL	22.0 kN
PISTON THRUST (OIL PRESSURE AT 4.0 MPa)	PUSH	32.8 kN
	PULL	28.6 kN
MAX. OPERATION PRESSURE	4.0 MPa	
MAX. SPEED	6000 min <sup>-1</sup>	
MASS	11.0 kg	
MOMENT OF INERTIA	0.026 kg·m <sup>2</sup>	
OIL LEAKAGE ISO VG 32 50°C 3.0MPa	3.0 L/min	

**Belong 付属品**

- 1. 六角穴付ボルト M8x70 : 6ヶ
- Hex. socket head cap screw M8x70 : 6 pcs.
- 2. ホースニップル  $\phi 33$  : 1ヶ
- Hose nipple  $\phi 33$  : 1 pce.

CAREER		SCALE	TYPE	SR1146
APPROVAL	INSPECTION	DRW	3RD ANGLE	ROTARY HYDRAULIC CYLINDER
		DATE		NAME
				SR1146
				OUTSIDE VIEW
Kitagawa Corporation			DRW NO.	61R297744 $\frac{1}{1}$