



SPECIFICATIONS	
PISTON DIA	165 mm
PISTON STROKE	23 mm
PISTON THRUST (油圧力 3.3 MPa)	PUSH 45.3 kN
	PULL 43.0 kN
PISTON THRUST (油圧力 4.0 MPa)	PUSH 56.4 kN
	PULL 53.6 kN
MAX. OPERATION PRESSURE	4.0 MPa
MAX. SPEED	4500 min ⁻¹
MASS	23.5 kg
MOMENT OF INERTIA	0.084 kg · m ²
OIL LEAKAGE ISO VG 32 50°C 3.0 MPa	4.3 L/min

For B-210
B-210用

- Belong 付属品**
- 1. 六角穴付ボルト M10x80 : 6ヶ
Hex. socket head cap screw M10x80 : 6 pcs.
 - 2. ホースニップル $\phi 33$: 1ヶ
Hose nipple $\phi 33$: 1 pce.

CAREER	SCALE	TYPE	SR1675
APPROVAL	INSPECTION	DRW	3D
Kitagawa Corporation	DATE	3RD ANGLE	2:3
NAME	SR1675	ROTARY HYDRAULIC CYLINDER	
NAME	SR1675	OUTSIDE VIEW	
DRW NO.	61R297745	1/1	