



**SPECIFICATIONS**

PISTON DIA	165 mm	
PISTON STROKE	23 mm	
PISTON THRUST (OIL PRESSURE AT 3.3 MPa)	PUSH	45.3 kN
	PULL	43.0 kN
PISTON THRUST (OIL PRESSURE AT 4.0 MPa)	PUSH	56.4 kN
	PULL	53.6 kN
MAX. OPERATION PRESSURE	4.0 MPa	
MAX. SPEED	4500 min <sup>-1</sup>	
MASS	24.5 kg	
MOMENT OF INERTIA	0.086 kg · m <sup>2</sup>	
OIL LEAKAGE ISO VG 32 50°C 3.0MPa	4.3 L/min	

**Belong 付属品**

- 六角穴付ボルト M10x80 : 6ヶ  
Hex. socket head cap screw M10x80 : 6 pcs.
- ホースニップル  $\phi 33$  : 1ヶ  
Hose nipple  $\phi 33$  : 1 pce.

CAREER		SCALE	TYPE	SR1670
		2:3	NAME	ROTARY HYDRAULIC CYLINDER
APPROVAL	INSPECTION	DRW 3D	NAME	SR1670 OUTSIDE VIEW
			DRW NO.	61R298123 0 1/1
Kitagawa Corporation		DATE		