



SPECIFICATIONS

PISTON DIA	165 mm	
PISTON STROKE	23 mm	
PISTON THRUST (OIL PRESSURE AT 3.4 MPa)	PUSH	47.8 kN
	PULL	43.0 kN
PISTON THRUST (OIL PRESSURE AT 4.0 MPa)	PUSH	56.4 kN
	PULL	50.7 kN
MAX. OPERATION PRESSURE	4.0 MPa	
MAX. SPEED	4500 min ⁻¹	
MASS	23.5 kg	
MOMENT OF INERTIA	0.084 kg·m ²	
OIL LEAKAGE ISO VG 32 50°C 3.0MPa	4.3 L/min	

For B-210
B-210用

Belong 付属品

- 1. 六角穴付ボルト M10x80 : 6ヶ
Hex. socket head cap screw M10x80 : 6 pcs.
- 2. ホースニップル $\phi 33$: 1ヶ
Hose nipple $\phi 33$: 1 pce.

6xM10取付ボルト (等配)
Tighten bolts
(Equi-spaced)

C (1:3)

CAREER			SCALE	TYPE	SR1677
APPROVAL	INSPECTION	DRW	3D	NAME	ROTARY HYDRAULIC CYLINDER
Kitagawa Corporation			DATE	3RD ANGLE	SR1677 OUTSIDE VIEW
				DRW NO.	61R298132 0 1/1 P